



Zebra® QLn™ Series Healthcare Printers



SEE MORE. DO MORE.



Part of a Complete Solution for Mobile Specimen Collection

Mobile printing enables users to label bedside specimens and samples at the point of collection, reducing the risk of errors and adverse events.*

Zebra's QLn Series Healthcare printers are small and light enough to be easily carried on a belt clip or trolley and deliver labels at the point of care. This saves time and money and improves the patient experience.

The QLn220™ and QLn320™ Healthcare printers — an extension of Zebra's user-friendly QLn series printers — were designed specifically with healthcare facilities' needs in mind. To safeguard patient health, all tools that come into contact with patients must be clean of any potential germs, blood or other infectious liquids. However, cleaners can be harsh. Our healthcare printers are constructed using durable, disinfectant-ready materials so they can be cleaned quickly and easily between each use.

With Zebra's QLn series printers, developed especially for healthcare, you can:

- Collect bedside specimens and create an associated label directly at the point of collection
- Easily manage, maintain and upgrade all of your print devices virtually with Zebra's Link-OS® environment
- Control printer configurations and ensure consistency in format outputs and printed materials with our Profile Manager app
- Reduce service calls
- Print labels that meet the Clinical and Laboratory Standards Institute® (CLSI) harmonization standard
- Eliminate risk, save time and gain peace of mind

Trust Zebra to help you deliver the quality care your patients expect, and the efficiency you need.

Ideal for These Patient Bedside Applications

- Specimen/Sample Labeling
- Patient Records Labeling

Link-OS®



* The mislabeling of samples causes an estimated 150,000 adverse events each year—in the United States alone.

QLN SERIES HEALTHCARE PRINTERS: DESIGNED TO MEET THE DEMANDS OF YOUR HEALTHCARE FACILITY

Easy to Implement and Manage

With Zebra's Link-OS environment, hospital IT staff can manage individual printers or groups of printers remotely via a web browser. Using the Profile Manager app, IT staff can expedite initial implementation, automate firmware uploads, resolve issues remotely and eliminate the time it takes to update programming on a printer-by-printer basis. And, if desired, users can alter printer settings from the front panel. Connect QLn printers to a wired Ethernet network via the QLn Ethernet cradle to enable easy, remote management.

Easy to Connect

The QLn series offers the most in connectivity options with faster data transfer rates and greater range. Incorporating WLAN (802.11 a/b/g/n dual band) and Bluetooth® 3.0, these printers also offer Near Field Communication (NFC) for Print Touch™ features, such as immediate support to resolve printing challenges. To meet the increasing demand for mobile printing from different operating systems, QLn printers are "Made for iPod®/iPhone®/iPad®" certified and also support Android™ and Windows® devices via Multiplatform SDK apps.

Easy to Carry

Weighing less than 2lbs and featuring a small footprint, the QLn220 and QLn320 are light enough to carry on a belt clip and fit easily on a cart or trolley.

Easy to Use

Both the QLn220 for print widths up to 2 inches and the QLn320 for 3-inch-wide printing feature an easy-to-read display with a large, high-resolution screen. A variety of proactive alerts helps keep the printers up and running, and the Link-OS Print Touch app gives hospital staff instant access to product support and how-to videos.

Easy to Accessorize

Redesigned especially for healthcare, the QLn220 and QLn320 feature a more desired healthcare color palette with a matching belt clip and battery, similar to that of the HC100,™ for a common look and feel.

Easy to Clean

Cleaning agent ingredients that are safe to use on QLn Healthcare printers:

- Isopropyl and Ethyl alcohol (including wipes)
- Ammonium
- Hydrogen peroxide
- Phosphoric acid
- Bleach/sodium hypochlorite
- Mild dish soap

Recommended cleaning agents include:

- **Windex® Blue**
(or Isopropyl alcohol-based equivalent)
- **CaviCide®**
(or Isopropyl and Ethyl alcohol-based equivalent)
- **Lysol® Healthcare**
(or hydrogen peroxide-based equivalent)
- **Wescodyne®**
(or phosphoric acid-based equivalent)
- **409® Glass and Surface Cleaner**
(or dimethyl benzyl ammonium chloride or other ammonium-based equivalent)



GENUINE ZEBRA™ SUPPLIES

Genuine Zebra Supplies

Ensure consistent print quality, reduce downtime and increase productivity in your printing process with Genuine Zebra supplies. We manufacture each supplies product with the exact same materials every time so you always get crisp, readable and scannable output without needing to adjust the printer darkness setting between rolls.

Zebra's IQ Color labels were developed to meet CLSI's approved standard for specimen collection and give clinicians the ability to highlight the priority status and container type in red as indicated at the left side of the label. Zebra also offers standard paper labels and moisture-resistant polypropylene labels for use with samples that need to be placed in ice upon collection.



ZebraCare™ Service

Increase printer uptime and reduce lost productivity and unbudgeted repair costs by selecting a ZebraCare Depot service agreement. A cost-effective means of planning and budgeting your annual maintenance expenditures, your agreement ensures that trained Zebra technicians will bring your printer back to factory specifications. Zebra offers a variety of plans to fit your budget and business needs.

Available Accessories

Existing accessories are compatible with this new QLn Series Healthcare printers:

- Ethernet cradle (single or 4-bay)
- IEC 60601-certified AC adapter for medical environments
- Smart charger
- Extended-capacity Li-Ion smart battery
- Quad battery charger
- Carrying straps/cases

Certifications

Many of Zebra's healthcare solutions, including the QLn220 and QLn320, are certified and recommended by all of the leading Electronic Health Records (EHR) providers.

Wi-Fi Alliance Certification: Ensures compatibility with Wi-Fi® Certified network products

SPECIFICATIONS AT A GLANCE*

Printer Name

QLn220 (Healthcare)
QLn320 (Healthcare)

Standard Features

- Includes disinfectant-ready plastics in a lighter healthcare color scheme
- Apple® iOS, Android, Windows Mobile and BlackBerry® connectivity
- Direct thermal printing of barcodes, text and graphics
- CPCL, EPL™ and ZPL® programming languages
- 256MB Flash supports downloadable programs, receipt formats, fonts and graphics (64MB available for user storage)
- 2450mAh (nominal) 18.1 Wh removable, rechargeable Li-Ion battery
- Built-in battery charger
- IEC 60601-certified AC adapter for medical environments
- Serial and USB ports (both support strain relief)
- Belt clip for unobtrusive and convenient printing (not compatible with extended capacity battery)
- Black mark and gap media sensing using fixed center position sensors
- Easy-to-use peel and present mode
- Label present sensor for issuing labels one at a time
- Tear bar for easy media dispensing
- Center-loading media locking for variable roll widths
- “Clamshell” design for easy media loading
- Management: Mirror, SNMP, Web server, Profile Manager, AirWatch® and Wavelink Avalanche®
- Large, easy-to-read LCD control panel (240 x 128 pixels)
- LCD can be customized using WML (text and icons)
- 5-way navigation buttons, two software defined keys
- Printer alerts on the display, help menus
- Tolerance of multiple drops from 5/ 1.52m to concrete
- IP43 dust- and water-resistance rating (IP54 with soft case)
- 400MHz 32-bit ARM processor
- XML support
- Supports vertical and horizontal printing
- Printers can be used in any orientation
- QR barcode links to web-based help pages
- Zebra Print Touch simplifies Bluetooth pairing and launches web-based help pages with Near Field Communication (NFC) enabled devices
- Label odometer
- Real-time clock

Printer Specifications

Resolution

203dpi/ 8dots per mm

Memory

128MB RAM; 256MB Flash (standard)

Print Width

- QLn220: 1.9”/ 48mm
- QLn320: 2.9”/ 72mm

Print Length

- Min. : 0.5”/ 12.7mm
- Max. : 32”/ 813mm

Print Speed

Up to 4”/ 102mm per second

Media Sensors

Black mark and gap media sensing using fixed center position sensors; label present sensor for issuing labels one at a time

Operating Characteristics

Environment

- Operating Temperature: 32°F/ 0°C ~ 122°F/ 50°C
- Storage/Transport Temperature: -13°F/ -25°C ~ 158°F/ 65°C
- Operating Humidity: 10% ~ 90% non-condensing
- Storage Humidity: 10% ~ 90% non-condensing

Agency Approvals

- Emissions: FCC Part 15, Subpart B, EN55022 Class-B, EN60950, EN55024 and VCCI class B
- Susceptibility: EN55024, EN61000-4-2, EN61000-4-3, EN61000-4-4, and EN61000-4-5
- Safety: CE, UL, TUV, CSA

Media Characteristics

Media Width

- QLn220: 0.63”/ 16mm to 2.18”/ 55.4mm
- QLn320: 1”/ 25mm to 3.125”/ 79mm

Media Length

- QLn220: 0.5”/ 12.7mm to 32”/ 813mm
- QLn320: 0.5”/ 12.7mm to 32”/ 813mm or continuous

Maximum Media Roll Size

- QLn220: 2.2”/ 55.9mm OD on a 0.75”/ 19mm or 1.375”/ 34.9 mm
- QLn320: 2.6”/ 66mm OD on a 0.75”/ 19mm or 1.375”/ 34.9mm

Media Thickness

- QLn220: 2.3mil to 5.5mil tag stock & 6.5mil label stock
- QLn320: 2.3mil to 5.5mil tag stock & 6.5mil label stock

Media Types

Die-cut labels and tags, linerless labels, receipt paper, black bar and gap sensing

Physical Characteristics

	QLn220	QLn320
Width:	3.5”/ 89mm	4.6”/ 117mm
Height:	2.75”/ 70mm	3.3”/ 84mm
Depth:	6.5”/ 165mm	6.8”/ 173mm
Weight:	1.25 lbs/ 0.57kg with battery	1.6 lbs/ 0.72kg with battery

Note: The Extended Capacity Li-Ion smart battery option adds 0.20 lbs/ 0.09 kg to the weight and 0.6”/ 16mm to the height of either QLn series printer.

Link-OS Solutions

Software Tools

- Document Design:** Quickly design a customized print solution using your business data and Zebra’s intuitive, plug-and-print design tools.
- Device Integration:** Zebra offers apps and products designed to help you integrate Zebra devices into your existing systems.
- Device Management:** Manage your print operations locally and globally with Zebra’s suite of device management tools.
- Developer Tools:** Provides you the tools you need to create your own apps, including documentation, source code, programming languages, templates and more.

Firmware

- CPCL, EPL and ZPL programming languages
- ZBI 2.x™ — powerful programming language that lets printers run standalone applications, connect to peripherals, and much more

Fonts/ Graphics/Symbologies

Fonts and Character Sets

- Standard Fonts: 25 bitmapped, 1 smooth, scalable (CG Triumvirate Bold Condensed)**
- Optional Fonts: downloadable bitmapped/scalable fonts
- International Character Sets (optional): Chinese 16x16 (traditional), 16x16 (simplified); Japanese 16x16, 24x24; Korean Mincho

CPCL Barcode Symbologies

- Barcode Ratios: 1.5:1, 2:1, 2.5:1, 3:1, 3.5:1
- Linear Barcodes: Code 39, Code 93, UCC/EAN128, Code 128, Codabar (NW-7), Interleaved 2-of-5, UPC-A, UPC-E, 2 and 5 digit add-on, EAN-8, EAN-13, 2 and 5 digit add-on
- 2-Dimensional: PDF417, MicroPDF417, MaxiCode, QR Code, GS1/DataBar™ (RSS) family, Aztec, MSI/ Plessey, FIM Postnet, Data Matrix, TLC39

Communication and Interface Capabilities

- ZebraNet® 802.11n option — provides 802.11a/b/g/n WLAN support with:
 - WEP (PSK only), TKIP and AES encryption
 - WPA and WPA2
 - 802.1x (with WPA or WPA2 only): EAP-FAST, EAP-TTLS, EAP-TLS, PEAP, LEAP
 - 802.11d and 802.11i
 - Simultaneous Bluetooth 3.0 dual radio
 - Wi-Fi Certification
 - Fast roaming using PMK caching, CCKM or Fast Session resumption
- Bluetooth 3.0 radio
 - Security modes 1 – 4
 - “Made for iPod/ iPhone/ iPad” certified
 - Key Bonding
- 10/100 Ethernet support (via charging cradle)

Cabled Communications Specifications

- USB 2.0 full-speed interface (12Mbps)
- Mini-B connector with optional strain relief
- Serial interface: 14-pin RS-232C port for communication to terminal or other host up to 115.2 Kbps

Options and Accessories

Charging Options

- Charge the battery inside the printer using AC adapter (IEC 60601-certified for medical environments), Single cradle or Quad cradle
- Charge the battery outside the printer using Single smart charger or Quad charger

Optional Features and Accessories

- Linerless printing (with silicone platen roller only)
- ZBI 2.x
- Spare batteries
- 4300mAh (nominal) removable extended capacity Li-Ion battery (4-cell bump out pack)
- AC adapter
- SC2 smart battery single charger
- Quad battery charger
- Vehicle charger with cigarette lighter adapter
- QLn-EC — single bay Ethernet and charging cradle (not compatible with extended capacity battery)
- QLn-EC4 — quad bay Ethernet and charging cradle, with internal switch and stacking port (not compatible with extended capacity battery)
- Shoulder strap
- Hand strap
- Soft case (IP54 rating when used) — not compatible with extended capacity battery
- Printer stand for tabletop mounting
- Serial and USB cables with strain relief



ASIA-PACIFIC HEADQUARTERS

Zebra Technologies Asia Pacific Pte Ltd

71 Robinson Road, #05-02/03, Singapore 068895 T: 65 6858 0722 F: 65 6885 0838

Asia-Pacific Sales Representations: Australia, China, Hong Kong, India, Indonesia, Japan, Malaysia, New Zealand, Philippines, South Korea, Singapore, Thailand, Taiwan, Vietnam

Other Locations

USA: California, Georgia, Illinois, Rhode Island, Texas, Wisconsin

Europe: France, Germany, Italy, the Netherlands, Poland, Spain, Sweden, Turkey, United Kingdom

Latin America: Brazil, Florida (LA Headquarters in USA), Mexico

Middle East & Africa: Dubai, South Africa

SEE MORE.
DO MORE.

www.zebra.com

(5/14)AP

*Specifications subject to change without notice. **Contains UFST from Agfa Monotype Corporation. ©2014 ZIH Corp. Link-OS, Zebra, the Zebra head graphic, ZebraNet and ZPL are trademarks of ZIH Corp., registered in many jurisdictions worldwide. The QLn series and all product names and numbers are Zebra trademarks. All rights reserved. Android and the Android Robot are trademarks of Google Inc. iPad, iPhone and iPod are trademarks of Apple Inc., registered in the US and other countries. Wi-Fi and the Wi-Fi logo are registered trademarks of Wi-Fi Alliance. Windows and the Windows logo are registered trademarks of Microsoft Corporation in the United States and other countries. All other trademarks are the property of their respective owners.